

Genie Z45/25 J



Specifications

- **Working height:** 51 ft 6 in (15.87 m)
- **Platform height:** 45 ft 6 in (13.87 m)
- **Horizontal reach:** max 25 ft (7.62 m)
- **Up/over clearance - at platform:** 23 ft 2 in (7.06 m)
- **Safe working load:** 500 lbs (227 kg)
- **Platform rotation:** 180 Degrees
- **Turntable rotation:** 355° non-continuous
- **Operating width:** 5 ft 10.5 in (1.79 m)
- **Wheelbase:** 6 ft 8 in 21.03 m
- **Ground clearance:** center 9.5 in (.24 m)
- **Unladen weight: for bi energy** 16,100 lbs (7,303 kg)
- **Transit height:** 6 ft 7 in (2 m)
- **Transit width:** 5 ft 10.5 in (1.79 m)
- **Transit length:** 18 ft 3 in (5.56 m)
- **Platform: L:** .76 m **W:** 1.83 m

Features & Options

With an extended reach, models with jibs, and a variety of outstanding performance features, the Z-45/25 DC/Bi-Energy handles the most challenging high-reach jobs.

The revolutionary Genie Bi-Energy system combines the quiet, emission-free and efficient operation of a

The logo features a stylized eagle with its wings spread wide, positioned to the left of the company name. The eagle is rendered in a dark grey color with a lighter grey shadow beneath it, giving it a three-dimensional appearance.

**EAGLE
ACCESS
PLATFORMS
LTD**

TELEPHONE: 01425 475185

MOBILE: 07800 598145

MOBILE: 07973 724260

FAX: 01425 483138

EMAIL: SCOTT@EAGLEPLATFORMSLTD.CO.UK

WEB: WWW.EAGLEPLATFORMSLTD.CO.UK

BLUE HAYES WOOLMER LANE BLASHFORD RINGWOOD HAMPSHIRE BH24 3PQ

48V DC machine with the versatility of a diesel generator powered machine to provide a boom that is ideal for indoor and outdoor applications.

- Quick and Maneuverable
- Unsurpassed Speed and Gradeability
- Dual Parallelogram Riser
- Large Platform with Hydraulic Rotation

Located at eye level with easy to understand controls and including auxiliary power, key switch, emergency stop, hour meter and all boom functions. The Drive Enable System informs operator when the drive and steer functions will move opposite controller movements.